

Dimensionering af FireProtect til standardprofiler - 30 min.

HE A-profil - brandklasse 30 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

HE B-profil - brandklasse 30 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

HE M-profil - brandklasse 30 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

Dimensionering af FireProtect til standardprofiler - 30 min.

IPE-profil - brandklasse 30 min.

Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	20	20	20	20	20	20
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
270	20	20	20	20	20	20
300	20	20	20	20	20	20
330	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20

INP-profil - brandklasse 30 min.

Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	20	20	20	20	20	20
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
380	20	20	20	20	20	20
400	20	20	20	20	20	20
425	20	20	20	20	20	20
450	20	20	20	20	20	20
475	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20

UNP-profil - brandklasse 30 min.

Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	20	20	20	20	20	20
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
350	20	20	20	20	20	20
380	20	20	20	20	20	20
400	20	20	20	20	20	20

Dimensionering af FireProtect til standardprofiler - 30 min.

UPE-profil - brandklasse 30 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	20	20	20	20	20	20
100	20	20	20	20	20	20
120	20	20	20	20	20	20
140	20	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20