

Dimensionering af FireProtect til standardprofiler - 60 min.

HE A-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	40	25	20	25	20	20
120	40	25	20	25	20	20
140	40	25	20	20	20	20
160	30	25	20	20	20	20
180	30	20	20	20	20	20
200	25	20	20	20	20	20
220	25	20	20	20	20	20
240	25	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

HE B-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	30	20	20	20	20	20
120	30	20	20	20	20	20
140	25	20	20	20	20	20
160	20	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

HE M-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
100	40	25	20	20	20	20
120	30	20	20	20	20	20
140	30	20	20	20	20	20
160	25	20	20	20	20	20
180	20	20	20	20	20	20
200	20	20	20	20	20	20
220	20	20	20	20	20	20
240	20	20	20	20	20	20
260	20	20	20	20	20	20
280	20	20	20	20	20	20
300	20	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
400	20	20	20	20	20	20
450	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20
650	20	20	20	20	20	20
700	20	20	20	20	20	20
800	20	20	20	20	20	20
900	20	20	20	20	20	20
1000	20	20	20	20	20	20

Dimensionering af FireProtect til standardprofiler - 60 min.

IPE-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	80	60	50	60	50	40
100	60	50	40	50	40	30
120	60	50	40	50	40	25
140	50	40	30	50	40	25
160	50	40	30	40	30	25
180	50	40	25	40	30	25
200	50	40	25	40	25	25
220	40	30	20	30	25	20
240	40	30	20	30	20	20
270	40	25	20	30	20	20
300	30	25	20	25	20	20
330	30	20	20	25	20	20
360	30	20	20	25	20	20
400	25	20	20	20	20	20
450	25	20	20	20	20	20
500	25	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20

INP-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	60	50	40	50	50	30
100	60	50	40	50	40	25
120	50	40	30	40	30	20
140	50	40	25	40	30	20
160	40	30	20	40	25	20
180	40	30	20	30	20	20
200	40	25	20	30	20	20
220	30	25	20	25	20	20
240	30	20	20	25	20	20
260	25	20	20	20	20	20
280	25	20	20	20	20	20
300	25	20	20	20	20	20
320	20	20	20	20	20	20
340	20	20	20	20	20	20
360	20	20	20	20	20	20
380	20	20	20	20	20	20
400	20	20	20	20	20	20
425	20	20	20	20	20	20
450	20	20	20	20	20	20
475	20	20	20	20	20	20
500	20	20	20	20	20	20
550	20	20	20	20	20	20
600	20	20	20	20	20	20

UNP-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	50	40	25	40	30	20
100	50	40	25	40	30	20
120	40	30	20	40	25	20
140	40	30	20	30	25	20
160	40	30	20	30	20	20
180	40	25	20	30	20	20
200	40	25	20	30	20	20
220	30	20	20	25	20	20
240	30	20	20	25	20	20
260	30	20	20	25	20	20
280	30	20	20	25	20	20
300	25	20	20	20	20	20
320	20	20	20	20	20	20
350	20	20	20	20	20	20
380	20	20	20	20	20	20
400	20	20	20	20	20	20

Dimensionering af FireProtect til standardprofiler - 60 min.

UPE-profil - brandklasse 60 min.						
Isoleret	4-sidet			3 sidet		
T-krit °C	450	500	550	450	500	550
Profilnr.						
80	50	40	30	40	30	20
100	50	40	30	40	30	20
120	50	40	25	40	30	20
140	50	40	25	40	30	20
160	50	40	25	40	25	20
180	40	30	20	40	25	20
200	40	30	20	30	25	20
220	40	25	20	30	20	20
240	40	25	20	30	20	20
260	30	25	20	30	20	20
280	30	20	20	25	20	20
300	25	20	20	20	20	20
320	25	20	20	20	20	20
340	20	20	20	20	20	20