

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
(Construction Products Regulation)

### Nr. DoP-DE-floor 4031

1. *Unique identification code of the product-type:*  
**weber.floor 4031**  
**CT-C25-F7; Polymer-modified** according to DIN EN 13813
2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*  
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
Cementitious screed for use in floor construction internally
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*  
Saint-Gobain Weber GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf  
[www.sg-weber.de](http://www.sg-weber.de)
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
not applicable
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
AVCP System 3 (Reaction to fire)  
AVCP System 4
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
The notified body SP Technical Research Institute of Sweden, identification number No. 0402, performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued: test report No. PX26920.
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A 2 <sub>n</sub> -s1	DIN EN 13813:2002
Release of corrosive substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C 25	
Flexural strength	F 7	
Wear resistance	NPD	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, July 11, 2013  
(Place and date of issue)

Bruno Reisch  
(Signature)

Annex  
Material safety data sheet weber.floor 4031