

# DECLARATION OF PERFORMANCE

## DoP N° PLF001

### 1. Unique identification code of the product-type

PLFT001

Product name:

Rigitone® Edge 12/25 Q OT  
Rigitone® Edge 12/25 Q BT  
Rigitone® Edge 12/25 Q WT  
Rigitone® Edge 12-20/66 OT  
Rigitone® Edge 12-20/66 BT  
Rigitone® Edge 12-20/66 WT  
Rigitone® Edge 8/18 OT  
Rigitone® Edge 8/18 BT  
Rigitone® Edge 8/18 WT  
Rigitone® Edge 8-15/20 OT  
Rigitone® Edge 8-15/20 BT  
Rigitone® Edge 8-15/20 WT  
Rigitone® Edge 8-15-20 Super OT  
Rigitone® Edge 8-15-20 Super BT  
Rigitone® Edge 8-15-20 Super WT  
Rigitone® Edge 8/18 Q OT  
Rigitone® Edge 8/18 Q BT  
Rigitone® Edge 8/18 Q WT

Traceability: see production date on stack label and/or on the product

### 2. Intended use/es:

Gypsum board product from reprocessing for use in wall, ceiling and floor applications

### 3. Manufacturer:

Placoplatre  
Tour Saint-Gobain  
12, place de l'Iris  
92400 Courbevoie  
<http://www.placo.fr>

### 4. Authorised representative:

Not applicable

### 5. System/s of AVCP:

AVCP System 3 - reaction to fire  
AVCP System 4 - for the other characteristics

### 6. a/ Harmonised standard:

EN 14190: 2014

Notified body/ies:

CSTB (Notified body n° 0679) issued reports relating to System 3 classification requirements for reaction to fire.

**b/ European Assessment Document:** Not applicable

European Technical Assessment: Not applicable

Technical Assessment Body: Not applicable

Notified body/ies: Not applicable

# DECLARATION OF PERFORMANCE

## DoP N° PLF001

### 7. Declared performance/s

Essential Characteristics	Performance	AVCP
Shear strength ( $\tau$ ) ( for stiffening timber framed external walls and timber roof truss structures)	NPD	4
Reaction to Fire (R2F)	A2-s1,d0 - (C.4)	3
Water vapour permeability (For moisture diffusion control)	NPD	4
Stability of ceiling element	NPD	4
Flexural strength (F)	NPD	4
Impact resistance ( $\rightarrow$ ) <sup>*</sup>	See manufacturer's literature <a href="http://www.placo.fr">www.placo.fr</a>	4
Direct airborne sound insulation (in end use conditions) <sup>*</sup>		4
Acoustic absorption (in end use conditions) <sup>*</sup>		4
Thermal conductivity $\lambda$	NPD	4
Dangerous Substances (DS)	NPD	4

\* These characteristics are system dependent and will be provided in manufacturer's literature based up to intended use.

Performance declared is for the system of which the product is a part

"NPD" (No Performance Determined).

### 8. Appropriate Technical Documentation and/or Specific Technical Documentation

Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Christian Bougeon**

Directeur général Placoplatre

A Courbevoie, le 26/07/2022

