

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
(Construction Products Regulation)

Nr. DoP-DE-therm 309

1. *Unique identification code of the product-type:*
weber.pas therm 309
Factory-made organic render and plaster according to DIN EN 15824
2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Render and plaster based on organic binder used for external or internal covering on walls, columns, partitions and ceilings
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
Saint-Gobain Weber GmbH
Schanzenstr. 84
D-40549 Düsseldorf
www.sg-weber.de
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
not applicable
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 3 (Reaction to fire)
System 4
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
The notified body Materialprüfungsamt Nordrhein-Westfalen, identification number No. 0432, performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued: test report No. 230007902-4.
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Water vapour permeability	V ₂ medium	DIN EN 15824:2009-10
Water absorption	W ₃ low	
Adhesion	≥ 0,3 MPa	
Durability	NPD	
Thermal conductivity $\lambda_{10,dry,mat}$ (Tab. value EN 1745)	NPD	
Reaction to fire	Euroclass A2-s1, d0 (on mineral substrates)	
Dangerous substances	NPD	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, *July 11, 2013*
(Place and date of issue)

Bruno Reisch
(Signature)

Annex
Material safety data sheet weber.therm 309