

Saint-Gobain API BV
Newtonweg 1
3846 BJ Harderwijk
The Netherlands

P.O. Box 1
3840 AA Harderwijk
The Netherlands
T +31 (0)341 474600
F +31 (0)341 474626
E sales@api.nl
www.api.nl

Chamber of Commerce
08015950
BTW NL004318894.B.01

Declaration of Performance 0007-155E

Quick-Lock 24

1. Unique identification of product: Quick-Lock®
2. Identification of the construction product components:
Quick-Lock 24/32, Quick-Lock 24/38 RE, Quick-Lock 24/38, Quick-Lock 24/38 Unipro, Quick-Lock 24/38 TR, Quick-Lock 24/60.
3. Intended use: Suspended ceiling substructure component for use internally in buildings.
4. Manufacturer: Saint-Gobain API BV Newtonweg 1 Harderwijk The Netherlands
www.api.nl
5. Authorized representatives: n.a.
6. System of assessment and verification of performance:
 - 6.1. Loadbearing capacity: System 3
 - 6.2. Reaction to fire: Coil-coated steel system 3, Galvanized steel system 4
 - 6.3. Durability: System 4
7. Harmonized standard covering the construction product:
EN 13964:2014 suspended ceilings:
 - 7.1. Loadbearing capacity: Tests carried out by NB0432 MPA Dortmund;
NB1153 TNO Delft
 - 7.2. Reaction to fire: Galvanized steel Commission decision 96/603/EC; Coil-coated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251,
 - 7.3. Durability: EN 13964 Table 8
8. European Technical Assessment: n.a.

QUICK-LOCK® Ceiling systems

9. Declared performances:

	7.1 Load bearing capacity						7.2	7.3
	Deflection	Span min/max mm	Admissible bending moment (M _{adm}) Nm	Maximum bending moment (M _u) Nm	Bending stiffness (EI) Nm ²	Notified body	Reaction to fire	Durability
Quick-Lock 24/32	Class 1	1000 / 1250	17,8	76,8	926	NB0432	Class A1	Class B
Quick-Lock 24/38 RE	Class 1	1000 / 1250	18,1	44,9	948,9	NB0432	Class A1	Class B
Quick-Lock 24/38	Class 1	1000 / 1250	27,0	106,3	1405	NB0432	Class A1	Class B
Quick-Lock 24/38	Class 1	1250 / 2500	13,4	33,5	1914	NB0432	Class A1	Class B
Quick-Lock 24/38 Unipro	Class 1	1200 / 1500	25,5	108,7	1594	NB0432	Class A1	Class B
Quick-Lock 24/38 TR	Class 1	1250 / 2500	18,0	48,7	2160	NB0432	Class A1	Class B
Quick-Lock 24/60	Class 1	1250 / 2500	37,7	94,1	5742	NB0432	Class A1	Class B

Tolerances and dimensions fulfil the requirements as specified in EN 13964 table 2.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer:



Per-Erik Velin
Managing Director
Harderwijk NL 01-06-2020